

IN THE CLAIMS


1. (Original) A top-pumped optical device comprising:
 - a substrate;
 - a lower cladding layer formed on the substrate;
 - a gain medium structure formed on the lower cladding layer and excited by absorbing pumping light; and
 - a light source disposed above the gain medium structure for pumping the gain medium structure by means of light directed downward therefrom,wherein a portion of the gain medium structure, which is included in a beam spot of the light source, has a larger area than other portions of the gain medium structure.
2. (Original) The top-pumped optical device as set forth in claim 1, further comprising an upper cladding layer formed on the gain medium structure, wherein the upper cladding layer is made of a material which transmits the light irradiated from the pumping light source.
3. (Original) The top-pumped optical device as set forth in claim 1, wherein the gain medium structure does not exhibit great absorption property in a signal wavelength band of the optical device, but exhibits great absorption property in other wavelength bands.
4. (Currently amended) The top-pumped optical device as set forth in claim 3, wherein the gain medium is made of one selected from the group consisting of a macromolecular substance doped with excited elements, a silica-based substance doped with excited elements and nano-crystals, a chalcogenide glass substance doped with excited elements, and a GaN or GaN-based substance doped with excited elements.
5. (Cancelled)

6. (Currently amended) The top-pumped optical device as set forth in claim [[5]] 4, wherein the excited elements are rare-earth elements.
7. (Original) The top-pumped optical device as set forth in claim 1, wherein the pumping light source is a LED.
8. (Original) The top-pumped optical device as set forth in claim 1, wherein the gain medium structure includes adiabatic portions between the portion having the larger area and other portions.
9. (Original) The top-pumped optical device as set forth in claim 1, wherein the pumping light source contacts a top surface of the upper cladding layer.
10. (New) A top-pumped optical device comprising:
a substrate;
a lower cladding layer formed on the substrate;
a gain medium structure formed on the lower cladding layer and excited by absorbing pumping light;
a light source disposed above the gain medium structure for pumping the gain medium structure by means of light directed downward therefrom,
wherein a portion of the gain medium structure, which is included in a beam spot of the light source, has a larger area than other portions of the gain medium structure, and
wherein the gain medium is made of a silica-based substance doped with rare-earth elements and nano-crystals.

Customer No. 20575

Respectfully submitted,


MARGER JOHNSON &
McCOLLOM, PC



Hosoon Lee
Registration No. 56,737

210 SW Morrison Street, Suite 400
Portland, OR 97204
(503) 222-3613

I hereby certify that this correspondence
is being transmitted to the U.S. Patent and
Trademark Office via facsimile number
571-273-8300, on April 24, 2006.



Hosoon Lee